



<b>Chemical system:</b>	Nickel-Metal Hydride, Precharged
<b>Designations:</b>	IEC HR6, ANSI 1.2H2
<b>Nominal Voltage:</b>	1.2V
<b>Nominal Capacity:</b>	2100 mAh
<b>Rated, Minimum Capacity:</b> (IEC/EN 61951-2)	2000 mAh
<b>Charging Condition:</b>	210 mA for 16h
<b>Maximum continuous discharge:</b>	4.0 A to 1.0 V
<b>Maximum intermittent discharge:</b>	6.0 A
<b>Minimum charging cycles:</b>	1000
<b>Average Weight:</b>	28.0 g
<b>Recommended storage temperature:</b>	5 – 20 °C
<b>Operating temperatures:</b>	0 – 50 °C
<b>Terminals:</b>	Flat contacts
<b>Jacket:</b>	PVC Label

Note:

- 1) No added Mercury / 99.9999% Mercury Free
- 2) No added Lead /99.999% Lead Free
- 3) No added Cadmium / 99.9999% Cadmium Free
- 4) No added PFOS (Perfluorooctane sulfonates)
- 5) This battery complies with ANSI C18, IEC 60086, and EU Directive 2006/66/EC, 2006/122/EC
- 6) Batteries are NOT subject to European RoHS regulations.
- 7) MSDS sheets are available on request from Strand Europe Ltd.
- 8) Charge or Discharge at extreme high or low temperature will significantly affect service and cycle life.
- 9) For best performance after long period of non-use, charge and discharge the battery several times.

